Environmental Issues Associated with the Use of Coal Tar-based Sealants: A Minnesota Perspective

Judy L. Crane, Ph.D.

Environmental Analysis and Outcomes Division Minnesota Pollution Control Agency St. Paul, MN

Green CiTTS Webinar January 25, 2011



Recent Newspaper Headlines

- New doubts cast on safety of common driveway sealant. *Extremely high levels of toxic chemical in coal tar found in booming suburb* (Jan. 16, 2011 Chicago Tribune,

 http://www.chicagotribune.com/health/ct-met-toxic
 - http://www.chicagotribune.com/health/ct-met-toxic-coal-tar-sealant-20110115,0,2601922.story?page=1)
- American urban lake pollution traced to parking lot seal coat (Dec. 5, 2010, McClatchy Washington Bureau, http://www.mcclatchydc.com/2010/12/05/vprint/104742/american-urban-lake-pollution.html)



Overview

- How coal tar-based sealcoat products contribute polycyclic aromatic hydrocarbons (PAHs) to urban waterways and why this is of concern;
- How the Minnesota Pollution Control Agency (MPCA) and MN State Legislature are addressing this issue; and
- What the preliminary results of a stormwater pond sediment study of the Minneapolis-St. Paul, MN metropolitan area reveal about the distribution of PAHs, the effects of


land use practices, and likely sources of PAHs to the study sites.




Properties of PAHs

- Are persistent organic pollutants and include hundreds of individual compounds. These compounds usually occur as mixtures with a range of physical/chemical characteristics.
- PAHs are found everywhere.
- Parent PAHs consist of only benzene rings fused together.
- Alkylated PAHs have alkyl substitutions added to the fused ring.





Benzo[a]pyrene (parent PAH)



2-methyl chrysene (alkylated PAH)

Why Are We Concerned About PAHs?

- Seven PAHs are classified as probable human carcinogens (Group B2);
- Other PAHs are known for their carcinogenic, mutagenic, and teratogenic properties;
- PAHs can cause skin tumors and other effects in fish; and
- Most bottom-dwelling aquatic invertebrates can't metabolize PAHs and are susceptible to a number of adverse effects.



Problem: Stormwater ponds in the Twin Cities are filling up with sediment, some of which are contaminated with PAHs.






Nonfunctioning stormwater ponds in Woodbury, MN




Coal Tar-based Sealcoats have Emerged as a Source of PAHs to Stormwater Ponds






PAH Pathways from Sealed Areas



PAH Sources to 40 U.S. Lakes (Van Metre and Mahler, 2010)





Coal tar sealcoat contributes about one-half of PAHs in sediment, followed by vehicle-related sources, and coal combustion.


University of New Hampshire (UNH) Study of PAHs in Stormwater Runoff from Sealcoated Pavements

- Watts et al. (2010) study published Nov. 2010 in Environmental Science & Technology.
- Study measured a 2-year release of PAHs in parking lot runoff.
- Determined coal tar-based parking lot sealcoat was a significant source of PAHs in stormwater runoff, and the presence of coal tar sealant increased the mass of PAHs released in runoff by over an order of magnitude.




UNH Study (continued)

• The study also found that even partial coverage of a drainage area by coal tar sealant resulted in measurable increases in PAH concentrations in sediment.






PAH White Paper available at: http://www.pca.state .mn.us/publications/ tdr-g1-07.pdf



The Role of Coal Tar-based Sealcoat Products as a Source of PAHs





Minnesota Pollution Control Agency



MPCA Approach

- The MPCA is using education and outreach to increase awareness of the PAH contamination problem in stormwater pond sediments;
- Agency staff recognize there are several sources of PAHs in urban environments that can contribute to the load of PAHs in stormwater ponds;
- In the MPCA's education efforts, the selection of sealcoat products is presented as a P2 (pollution prevention) decision that property owners and local units of government need to make.



Legislative Response to Issue

- The 2009 Minnesota Legislature provided the MPCA with funding to study this issue on July 1, 2009.
- Part of the funding related to developing best management practices. This included evaluating sampling and screening methods for good, costeffective techniques through a study of stormwater pond sediments in different land use categories (residential, commercial, and industrial areas) for PAHs and other contaminants of potential concern.



Study Objectives

- Determine the influence of urban watershed land uses on PAHs (and other contaminants) in stormwater pond sediments;
- Determine the applicability of an analytical screening technique (laser induced fluorescence—LIF), as well as simple chemical modeling, for conducting sediment assessments of stormwater ponds;



Tahoe Rd. North Pond (SWP09-11) in Woodbury,MN. Photo by Tim Nelson (Minnesota Public Radio)




Study Objectives


- Determine whether some emerging contaminants are present at detectable concentrations;
- Compare data to MPCA soil reference values (SRVs) and sediment quality targets (SQTs);
- Determine contaminants of concern; and
- Modify, if needed, sampling and dredge disposal recommendations for stormwater permittees.





Municipal Separate Storm Sewer System (MS4) Areas Regulated by the MPCA








Metro MS4 Areas Regulated by the MPCA

Metro Area Regulated MS4s








Residential Land Use



Commercial (up); Industrial (down)



Stormwater Pond Sample Locations



Field Sampling During October 2009



Photo by Anna Kerr (MPCA)



Photo by Judy Crane (MPCA)



Photo by Tim Nelson (Minnesota Public Radio)



PAH-Related Analyses

- Parent and carcinogenic PAHs were analyzed on all samples by Pace Analytical Services, Inc. using EPA 8270 by GC/MS-SIM;
- Semivolatile organic compounds (SVOCs) were analyzed on composite samples by Pace Analytical Services, Inc. using EPA 8270 by GC/MS;
- Parent and alkylated PAHs were analyzed on composite samples by Battelle using modified EPA methods (SW-846 3550 and EPA 8270) by GC/MS-SIM; and
- All sediment samples were screened using multiple LIF techniques by Dakota Technologies.




Results




Two industrial sites and one commercial site exceeded the Level II sediment quality target (SQT) value for total PAHs₁₃.

No significant differences (p = 0.085) between land uses due to one low industrial site concentration.






One commercial site exceeded the MPCA's Level 1 (residential) soil reference value (SRV) limit of >2.0 to <3.0B[a]P equivalents. Three sites exceeded the MPCA's Level 2 (industrial) SRV limit of >3.0 B[a]P equivalents.






Two industrial sites and one commercial site had PAH ESB toxic units exceeding 1.0.





Total PAHs₁₆ Can Be Used To Predict Total PAHs₃₄






Identifying Sources of PAHs with Environmental Forensic Techniques




Solving Mysteries




Comparison of Histogram Plots of PAHs








PAH Double Source Ratio Plot





PAH Double Source Ratio Plot








Quantitative techniques, like the U.S. EPA's contaminant mass balance model (EPA-CMB8.2), provide a more rigorous method for apportioning sources of PAHs.



How does the CMB Model Work?

- Incorporates published source profiles (fingerprints) for 12 PAHs;
- Figures out the best combination of sources to best match the receptor profile (lake sediment) by minimizing Chi-squared (X²);
- Provides estimated mass loading and uncertainty for each source.





PAH, low to high molecular weight; graphic from Peter Van Metre (USGS).

Assumptions of CMB Model (Li et al. 2003)

- 1. Composition of each source emission is consistent;
- 2. Chemical species do not react with each other or with the environment;
- 3. All sources that contribute significantly to the receptor have been identified and their chemical profile is known;
- 4. The composition of each source is linearly independent of other sources; and
- 5. Measurement uncertainties are random, uncorrelated, and normally distributed.



Summary Statistics of CMB Model Results*

Summary Statistics	R ²	CHI ²	% MASS	
Mean	0.9801	0.2412	101.0	
Wiodii	0.0001	0.2112	10110	
SD	0.00918	0.1163	1.2	
Minimum	0.9623	0.0814	99.1	
Maximum	0.9913	0.5744	103.3	



Source Apportionment of PAHs

		Coal Tar Sealant						
Site ID (SWP09-)	Land Use	Sum %	tunnel %	coal %	diesel %	oilbrn %	pinept %	gasoline %
01-C-alkP	residential	71.7	16.2	0	0	4.8	7.3	0
02-C-alkP	residential	52.0	39.5	0	0	7.1	0	1.4
06-C-alkP	residential	81.5	11.9	0	1.3	5.3	0	0
11-C-alkP	residential	85.6	14.0	0	0	0.4	0	0
14-C-alkP	residential	86.9	0	0	13.1	0	0	0
04-C-alkP	commercial	85.0	12.1	0	2.9	0	0	0
07-C-alkP	commercial	64.7	12.0	22.5	0	0	0.8	0
08-C-alkP	commercial	84.2	15.0	0	0.8	0	0	0
09-C-alkP	commercial	48.0	17.2	27.0	0	1.8	5.9	0
10-C-alkP	commercial	69.3	30.3	0	0	0.3	0	0
03-C-alkP	industrial	82.9	10.8	0	6.3	0	0	0
05-C-alkP	industrial	89.3	0	0	10.7	0	0	0
12-C-alkP	industrial	85.4	5.4	0	9.2	0	0	0
13-C-alkP	industrial	60.6	24.0	6.7	0	8.7	0	0
15-C-alkP	industrial	40.9	35.5	17.7	0	0.6	5.3	0



Coal Tar Sealant and Tunnel Air are the Most Prevalent Sources of PAHs in Metro Stormwater Pond Sediments

Summary Statistics	Coal Tar Sealant Sum %	Tunnel Air %
Mean	72.5	16.3
IVIOGIT	72.0	10.0
SD	15.9	11.7
Minimum	40.9	0
Maximum	89.3	39.5



Summary

- Three of the 15 stormwater ponds consistently exceeded high benchmark values for PAHs and related indices.
- Subsets of PAHs from the parent/alkylated group of PAHs (total PAHs₃₄) were not statistically different

based on land use, but additional statistical analyses need to be done to further evaluate any trends (e.g., remove the low industrial site as an outlier).





Summary (continued)

- The CMB model provided the most effective technique for apportioning sources of PAHs.
 - A combination of coal tar sealant dust and other weathered coal tar sealant sources were not inconsistent with the PAH profile for about 72% (mean value) of the PAH₃₄ data set.
 - Mobile sources of PAHs (represented by tunnel air) was consistent as another important source of PAHs to the PAH₃₄ data set.
- Additional analyses need to be done with the parent and carcinogenic PAH data set.



For Further Information

- Judy Crane, Ph.D. (MPCA): 651-757-2293 (voice) or judy.crane@state.mn.us.
- MPCA Web page on "Restriction on Coal Tarbased Sealants" at:

 http://www.pca.state.mn.us/index.php/water/water-types-and-programs/stormwater/municipal-stormwater/restriction-on-coal-tar-based-sealants.html.
- USGS Web page on "PAHs and Coal-Tar-Based Pavement Sealcoat" at: http://tx.usgs.gov/coring/allthingssealcoat.html.



Acknowledgments

- MPCA Field Sampling Planning and Assistance: Steve Hennes, Harold Wiegner, Alex Levchuk, Mike Anderson, Mary Jean Fenske, Dale Thompson, Anna Kerr, Louise Hotka, Mike Walerak, Steven Weiss, Jordan Donatell, and Jon Janke;
- MSTM Access Sediment Database Updates: Sara Mueller (MPCA);
- GIS Assistance: Kris Parson (MPCA);
- QA/QC Assistance: Sandy McDonald (MPCA);



Acknowledgments

• MS4 Municipalities Included in Study: Cliff Aichinger (City of North St. Paul), Scott Anderson and Steve Segar, P.E. (City of Bloomington), McKenzie Cafferty (City of Lakeville), Sharon Doucette (City of Woodbury), Nick Fleischhacker (City of Mounds View), James Hafner (City of Blaine), James Kosluchar, P.E. (City of Fridley), Michael Thompson, P.E. (City of Maplewood), Kerry Thorne (City of New Brighton), and John Sachi (City of South St. Paul);



Acknowledgments

- Battelle Project Manager: Kerylynn Krahforst;
- Pace Analytical Services Inc. Project Manager: Diane Anderson;
- Dakota Technologies Project Manager: Randy St. Germain;
- CMB Model Assistance: Peter Van Metre, Ph.D. and Barbara Mahler, Ph.D., P.G. (U.S. Geological Survey); and
- This project was funded by the Minnesota Legislature in 2009 as part of a bill contained in House File 1231 pertaining to the use of coal tar-based sealants.

